

GOTHIC CATHEDRAL WINDOW


DIORAMA 1/35

Instructions:

1. At first, clean all parts from flashes and grind them on their bearing surfaces to fit well.
2. To get all parts together tentative before cementing is highly recommended.
3. Cement all wall parts together according instruction drawing. Use some suitable glue (white glue).
4. Fill appropriate gaps with the putty prepared from the thinner gypsum paste. You can use the brush. Scrape superfluous gypsum off if the putty is partially dry and smooth the surface by a wet brush or finger.
5. Color finishing fully depends on your own consideration. Coat all gypsum parts by some varnish before the painting to decrease color consumption.

Návod sestavení:

1. Všechny díly nejprve učištěte od ořepů a pečlivě zbrúste všechny dosedací plochy.
2. Díly nejprve sesadte nasucho, abyste mohli ještě případně upravit dosedací plochy.
3. Dle obrázku slepte jednotlivé díly pomocí disperzního lepidla (Hercules, Gamafix, ...)
4. Při tmelení použijte jako tmelu řídkou sádku. K tomu můžete použít štětec. Částečně zaschnou přebytečnou sádku odstraníte a povrch vyhladíte vlhkým štětcem nebo prstem.
5. Před barvením je vhodné všechny sádkové díly natřít lakem, čímž snížíte savost podkladu a spotřebu barvy.



no.: 182